



EcolInnovation Technologies Inc., 231 rue Ste Marie, St-Louis de Gonzague, PQ, JoS-1To

Model	Heat Recovery Efficiency %	NRCan Program Energy Credits (kWh)	Nominal Diameter (mm)	Nominal Diameter (in)	Length (mm)	Length (in)	Heat Recovery Rate (kW)	CSA B55.1 Certified	Heat Recovery Rate (BTU/hr)	Pressure Loss (kPa)	Pressure Loss (psi)	Mass (kg)	Mass (lbs)
ECO-GFX2340	39	1418	75	3	1016	40	7	no	23896	9	1.3	9.8	21.1
TD336B	39.2	1425	75	3	914.4	36	7	yes	23884.98	9.1	1.3	10	22
TD338B	40.4	1469	75	3	965.2	38	7.2	yes	24567.41	9.7	1.4	10.4	22.88
TD340B	41.6	1513	75	3	1016	40	7.5	yes	25591.05	10.3	1.5	10.9	23.98
TD342B	42.8	1556	75	3	1066.8	42	7.7	yes	26273.48	10.9	1.6	11.2	24.64
TD344B	43.9	1596	75	3	1117.6	44	7.9	yes	26955.91	11.5	1.7	11.9	26.18
ECO-GFX2440	44.7	1625	102	4	1020	40	8.28	no	28300	14.1	2.1	13.3	29.4
TD346B	45	1636	75	3	1168.4	46	8.1	yes	27638.33	12.1	1.8	12.4	27.28
TD340-A	46	1673	75	3	1016	40	7.5	no	25603	55.2	8	9.84	21.7
TD348B	46	1673	75	3	1219.2	48	8.2	yes	27979.55	12.7	1.8	13	28.6
TD442B	46	1673	100	4	1066.8	42	8.3	yes	28320.76	9.6	1.4	16.8	36.96
TD350B	47	1709	75	3	1270	50	8.4	yes	28661.98	13.3	1.9	13.4	29.48
TD352B	48	1745	75	3	1320.8	52	8.6	yes	29344.4	13.9	2	14	30.8
TD354B	48.9	1778	75	3	1371.6	54	8.8	yes	30026.83	14.5	2.1	14.6	32.12
ECO-GFX2360	49	1782	75	3	1524	60	9.56	no	32636	14.5	2.1	14.8	32.6
TD356B	49.8	1811	75	3	1422.4	56	8.9	yes	30368.05	15	2.2	15.2	33.44
TD358B	50.7	1844	75	3	1473.2	58	9.1	yes	31050.47	15.6	2.3	15.8	34.76
ECO-GFX2460	51	1854	102	4	1016	60	9.81	no	33481	17.4	2.5	20.6	45.4
TD360B	51.5	1873	75	3	1524	60	9.2	yes	31391.69	16.2	2.3	16.5	36.3
TD362B	52.3	1902	75	3	1574.8	62	9.4	yes	32074.12	16.7	2.4	17	37.4
TD364B	53	1927	75	3	1625.6	64	9.5	yes	32415.33	17.3	2.5	17.7	38.94
TD366B	53.7	1953	75	3	1676.4	66	9.6	yes	32756.54	17.8	2.6	18.3	40.26
TD368B	54.4	1978	75	3	1727.2	68	9.7	yes	33097.76	18.4	2.7	18.9	41.58
TD370B	55	2000	75	3	1778	70	9.9	yes	33780.19	18.9	2.7	19.6	43.12
TD372B	55.6	2022	75	3	1828.8	72	10	yes	34121.4	19.5	2.8	20.3	44.66
TD460B	57.3	2084	100	4	1524	60	10.3	yes	35145.04	15.4	2.2	24.8	54.56
TD472B	58.4	2124	100	4	1828.8	72	10.5	yes	35827.47	18.5	2.7	29.9	65.78

*All units are CSA 55.2 safety certified. CDA 55.1 is performance and efficiency verification.