



AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report(s). This authorization also applies to the Multiple Listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The Certification Mark(s) may be applied only at the location of the Party Authorized to Apply Mark.

Applicant: EcolInnovation Technologies Inc
 231 Rue Ste-Marie
 St-Louis-de-Gonzague, QC J0S1T0
 Canada

Contact: Daniel Beauchemin

Phone: 888-881-7693

Fax: 888-899-1135

Email: dan@ecoinnovation.ca

Party Authorized to Apply Mark: See following page(s)

Evaluation Center: Intertek (Lachine)

Client Number: 178246

Authorized By: 
Jean-Philippe Kayl, Director of Certification

Intertek Testing Services NA, Inc.
 545 E. Algonquin Road, Ste H., Arlington Heights, IL 60005 USA
 Phone: 847-439-5667 Fax: 847-439-7320



Intertek

This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Testing Standard(s):	CSA B55.2 (2015) Ed.2
Product:	EcolInnovation Technologies Inc. - Drain Water Heat Recovery Pipe Model TD Series CSA B55.2

ATM for Report: G101070334;G103581073

ATM Issue Date: 1/13/2020

Listing Section(s): PLUMBING FITTINGS & ACCESSORIES

CSI Code(s): 22 30 00 Plumbing Equipment

Description:

PRODUCTS COVERED

Drain Water Heat Recover Pipe for residential or commercial use.

Models:

TD; followed by 2, 3, 4, or 6; followed by any number between 6 and 144, followed by A, B or P May be followed by 2 or 3; May be followed by C, D, E or PEX.

Thermodrain Model Nomenclature		
ABCCDEF		
A	TD	Thermo Drain Series
B	2	drain pipe diameter in inches
	3	
	4	
	6	
CCC	###	Length between 6 - 144 inches
D	A	1/2" copper tube
	B	3/4" copper tube
E	-	1 coil
	2	2 coils
	3	3 coils
F	-	default tube connection
	C	1" tube connection
	D	1-1/4" tube connection
	E	1-1/2" tube connection
	PEX	3/4" PEX

ECO-GFX followed by 1, 2, 3 or 4; followed by 2, 3, 4 or 6 followed by a number between 6 and 144; followed by; A, B, C, D, E

ECO-GFX Nomenclature		
ABCCDEF		
A	ECO-GFX	Series Brand
B	1	Number of coils
	2	
	3	
	4	
C	2	drain pipe diameter in inches
	3	

	4	
	6	
DDD	###	Length between 6 - 144 inches
E	A	1/2" tube connection
	B	3/4" tube connection
	C	1" tube connection
	D	1-1/4" tube connection
	E	1-1/2" tube connection
	P	3/4" PEX

TDH; followed by 2, 3, 4, or 6; followed by any number between 6 and 144, followed by B or P May be followed by 2 or 3; May be followed by C, D, E or PEX.

Thermodrain Model Nomenclature

ABCCCDEF

A	TDH	Thermo Drain high efficiency Series
	2	
	3	
B	4	drain pipe diameter in inches
	6	
C	###.#	Length between 6 - 144 inches. Last digit is decimal
D	B	3/4" copper tube
	-	1 coil
E	2	2 coils
	3	3 coils
	-	default tube connection
F	C	1" tube connection
	D	1-1/4" tube connection
	E	1-1/2" tube connection
	PEX	3/4" PEX

Party(s) Authorized by Manufacturer To Apply Mark:
None

Party(s) Authorized by Other Parties To Apply Mark:
None